

DIGITAL PHASE INDICATOR with open phase checker

8030



Features

- Phase indicator designed to check the presence of open phase and also the phase sequence by LED and buzzer at the same time.
- Small, lightweight, and portable.

Specifications

MODEL	Model 8030
Operational Voltage	200~480V AC
Time limit for continuous	200V: within 60 minutes 480V: within 4 minutes
Frequency Response	20~400Hz
Safety Standard	IEC61010-1 CAT. II 300V Pollution Degerr 2
Withstand Voltage	2200V AC for 1 minute
Dimensions	82(L)×59(W)×23(D)mm
Weight	200g approx.
Cord	1m(R: red S: white T: blue)
Accessories	Carrying Case pins for Test leads Instruction Manual

PHASE INDICATOR with open phase checker

8031



Features

- Phase indicator designed to check the presence of open phase and also the phase sequence by rotating disk and lamps.
- Can check a wide range of 3-phase power source from 110V to 600V.

Specifications

MODEL	Model 8031
Operational Voltage	110~600V AC
Time limit for continuous	> 500V: within 5 minutes
Frequency Response	50Hz/60Hz
Safety Standard	IEC61010-1 CAT. II 600V Pollution Degerr 2
Withstand Voltage	2200V AC for 1 minute
Dimensions	106(L)×75(W)×40(D)mm
Weight	350g approx.
Cord	1.5m(R: red S: white T: blue)
Accessories	9029(Carrying Case) Instruction Manual

ILLUMINOMETER

5200



Features

- $\pm 10\%$ accuracy. Permits a wide range of light measurements from 0 to 5,000 Lux.
- Swivel head that revolves 300 degrees will always allow the user to make measurements at an optimum viewing position.

Specifications

MODEL	Model 5200	
Ranges	Low	0~1000Lux(Red Scale)
	Ordinary	0~5000Lux(Black Scale)
	High	0~50000Lux(Black Scale w/10X Slide)
Accuracy	$\pm 10\%$ (tested by a standard parallel light tungsten lamp of 2854K colour temperature)	
Angle Allowance	30° 60°	Less than -3% Less than -10%
Correction of Slight Sensitivity	0~1000Lux: Use correction factor 0~5000Lux: Lux read directly	
Dimensions	112(L)×58(W)×27(D)mm	
Weight	135g approx.	
Accessories	8058(10X Slide) 8059(Lumidisc for Low measurement) 8060(Lumidisc for Ordinary measurement) 9040(Carrying Case) Instruction Manual	

DIGITAL ILLUMINOMETER

5201



Features

- Model 5201 is a highly portable and compact digital illuminometer for measuring illuminance from 0.1 to 19,990 Lux, with auto range switching.
- The digital display is held for a preset time (about 20 seconds) and, therefore, facilitates reading, recording and measuring in any direction.

Specifications

MODEL	Model 5201	
Ranges	0.1~19990Lux(automatic 3 range switching)	
Accuracy	$\pm 5\%$ rdg ± 3 dgt	
Measuring Time	3 times per second	
Temperature humidity characteristics	$\pm 3\%$ (at 20°C)	
Angular Incident Light Characteristics	Closely related to the Lambert's cosine law	
Spectral Response Characteristics	Closely related to the spectral luminous efficiency (of a standard observer).	
Power Source	6F22(9V)×1	
Dimensions	166(L)×68(W)×32(D)mm	
Weight	180g approx.	
Accessories	Photocell Cover Soft Carrying Case	6F22×1 Instruction Manual